

# **BIG GUY FIELD ROLLER**



## **Uses for a Field Roller:**

- Leveling Air Strip Runways
- Construction Sites
- Ground Compactor
- Rolling Rocks
- Leveling Roadways
- Packing Roads/Parking Lots
- Rolling Dirt Tracks
- Rolling Sod Fields

- Transportation option includes wheels for easy and quick movement without the necessity for a trailer.

- Clevis swivels option for safer control of field roller

- Category 2, 3 point also available

- Specs for Roller

- Will Custom size diameters and widths

- Tongue jacks standard

- 4 inch square tubing standard frame

- 5 inch square tubing standard on 3 point models

- Standard 6 bolt Ag implement wheels with 9.5L-15 8 ply tires on transport option.

- Wood Bearings- withstand more impact resistance with a proven history of over 25 years

## Field Roller Information

<b>SIZE</b>	<b>STEEL #</b>	<b>GALLONS</b>	<b>TOTAL LBS.</b>
24" x 1/4" x 4'	248	95	1,008
24" x 1/4" x 5'	310	116	1,240
24" x 1/4" x 6'	372	140	1,490
<hr/>			
30" x 3/8" x 5'	1,000	182	2,450
30" x 3/8" x 6'	1,100	220	2,850
30" x 3/8" x 7'	1,450	255	3,490
30" x 3/8" x 8'	1,675	292	4,020
<hr/>			
36" x 5/8" x 8'	2,750	445	6,000
36" x 3/4" x 8'	3,100	448	6,900
36" x 1" x 8'	3,900	448	7,700
36" x 3/4" x 10'	3,750	560	8,510
36" x 1" x 10'	4,750	560	9,510
36" x 3/4" x 12'	4,500	660	9,780
36" x 5/8" x 10'			
<hr/>			
43" x 11/16" x 8'	3,400	600	8,200
43" x 7/8" x 10'	5,000	750	11,000
<hr/>			
48" x 1" x 10'	6,179	940	13,970

weight not including the transport option or 3 point

**Additional charge for wheel kit on roller, includes cylinder and hoses**

**Cylinder and brakes additional**

**3" Cylinder has 14,137 lb. at 2000 psi**

**10,600 lb. at 1500 psi**